

# Sky Factory eScape™ 2.0 Digital Cinema

## DC-eScape-4123 Specifications

### Monitor:

49" (1245mm) Professional LED Edgelit LCD Monitor  
Resolution: 1920 x 1080

### Mounting Pan with Integrated Video-Audio Playback Equipment:

#### Mounting Pan

16 gauge steel, powder coated silver  
Provides one location for all playback equipment  
Protects eScape monitor and video-audio playback equipment, facilitates wiring,  
and provides ventilation for proper cooling  
Rough opening: call The Sky Factory for specific requirements.

Requires wire access from top during rough-in for power, signal cable to controller,  
and audio cable

Video-audio playback equipment

Simple plug-in module for additional content

### Wall Mounted Controller

Wired via Cat 6 cable

Simple illuminated push button operation

Fits in single gang outlet box

Low voltage mounting bracket provided

Keypad bezel available in white, almond or black

Standard Decora style faceplate available in white, almond, black or stainless steel

Other faceplate options available from Leviton

### Speakers

Two 2-way speakers

5.25" (133mm) dia. woofer, 0.5" (13mm) tweeter

7.95" (202mm) dia. trim ring comes in white, can be painted

6.625" (168mm) dia. rough opening, 3.2" (80mm) mounting depth

Tile bridge and backcan enclosure for drop ceiling applications

Backcan is UL Listed for air handling spaces

2.26 lbs (1.03kg)

### Cabling:

One plenum rated Cat 6 cable

Monitor location to wall mounted controller

Ends terminated with RJ45 connectors

35' (15.3m) standard, alternate lengths available if specified

Plenum rated speaker cable

monitor location to speaker locations

70' (30.6m) standard, or 35' (15.3m) +/- per speaker (alternate lengths available if specified)

### Trim:

Wood or brushed anodized clear or black aluminum (style and material selected by client)

Sizes vary with style and material selection

30 1/2" (775mm) to 33" (838mm) wide

49 1/16" (1246mm) to 52 1/16" (1333mm) high

7/16" (11mm) to 2" (51mm) deep from wall surface

### Electrical Requirements:

Total Power Consumption: 186 Watts Typ

Circuit Recommendations: a separate circuit is advisable

Power Surge Protection: recommended, but not provided

Operating Temperature: 32F ~ 94F (0C ~ 40C)

Operating Humidity: 20% ~ 80 % non-condensing

### Fixture Weight:

80.3 lbs + 10.1 to 28.9 lbs depending on trim choice

(36.4kg + 4.6 to 13.1kg depending on trim choice)

### Warranty:

2 year Sky Factory, Inc. limited warranty on entire system

eScape™

Recessed Wall Mount  
High-Definition (HD)  
Digital Cinema Virtual Window



### Viewable Area:

approx. 41" x 23" (1041mm x 584mm)  
depending on trim selection

### Video Content (provided):

8, 12 or 16 hours of full HD Resolution (1920 x 1080) videos

Recorded in Ultra HD

Mastered and played back in high bit-rate Full HD

More footage capacity available in the future

Simple plug-in module for additional content

**Notice: This product is NOT compatible with MRI and high energy particle imaging environments, such as Linac.**

**This document specifies product only.  
For rough opening and installation specifications,  
call the Sky Factory.**